

	Googol Power-Tech Co., Ltd.	Engine Model: QTA3240-G6	Engine Application: Generator
	Phoenix Lake Industrial Park, Yongchuan, Chongqing City, China		
	Tel: 86-23-49682222, Fax: 86-23-49683222	Engine Prime Power: 1665 KW	RPM: 1800
	5820 Central Ave, Unit 230, Riverside CA92504, U.S.A		
	Tel: 1-909-7436092 Fax: 1-909-9392093	Engine Standby Power: 1832 KW	Publication Date: 03-01-2015

Specifications:

Engine Model		QTA3240-G6
Speed	rpm	1800
Rating Output		
Standby Output (LTP)	kW	1832
Prime Output (PRP)	kW	1665
Engine Continuous Power (COP)	kW	1496
Fan Quantity		1
Fan Reduction	kW	72.0
Single Fan Reduction	kW	72.0
All Fans Reduction	kW	72.0
Engine Net Standby Output (LTP)	kW	1760
Engine Net Prime Output (PRP)	kW	1593
Engine Net Continuous Output (COP)	kW	1424
BMEP for Standby Output	bar	22.59
BMEP for Prime Output	bar	20.61
BMEP for Continuous Output	bar	18.65
Typical Generation Standby Output	kW	1650
Typical Generation Prime Output	kW	1500
Typical Generation Continuous Output	kW	1350
Max. step load acceptance, 1st step (% Prime Output)		35%
Basic Performance Datasheet		
Aspiration Type		Turbocharger, air-water aftercooler
Injection Type		Direct Injection
Configuration		Vee
No. of Cylinders		12
Displacement	l	53.1
Bore	mm	170
Stroke	mm	195
Compression Ratio		13.5:1
Piston Speed	m/s	11.7
Rotation Direction (from flywheel)		Counter Clockwise

Number of Flywheel Teeth		218
Flywheel House Size		SAE00-21
Lubrication System		
Lube Oil Specification		API-CF4
Oil Capacity	l	180
Max. Permissible Oil Temperature	°C	110
Oil Pressure Warning	kPa	300
Oil Pressure Shutdown	kPa	200
Cooling System		
Coolant Capacity for Engine	l	100
Max. Permissible Temperature	°C	90
Max. Coolant Warning Temperature	°C	95
Max. Coolant Shutdown Temperature	°C	98
Thermostat Open Temperature	°C	71
Radiator Cooling Flow	m ³ /min	3300
Flow of Cylinder liner Coolant pump	m ³ /h	57.6
Flow of aftercooler Coolant pump	m ³ /h	54.0
Heat dissipation (engine radiator)	kW	672
Heat dissipation (CAC)	kW	319
Heat dissipation (convection)	kW	100
Mode of Radiator(Aluminium core, 40°C environment's temp)		6400709
Mode of Radiator(Aluminium core, 50°C environment's temp)		6500709
Mode of Radiator(Aluminium core, 45°C environment's temp)		6450709
Fuel System		
Governor Type		Electrical
Engine Output at genset prime output	kW	1665
Fuel Consumption at 25% of genset prime output	l/h	124.63
Fuel Consumption at 50% of genset prime output	l/h	207.72
Fuel Consumption at 75% of genset prime output	l/h	296.88
Fuel Consumption at 100% of genset prime output	l/h	391.92
Lowest Fuel Consumption Ratio	g/kW.hr	196.55
Intake & Exhaust System (On Standby Output)		
Combustion Air Consumption	m ³ /min	166.5
Max. Intake Restriction	KPa	2
Exhaust Temperature (Before Turbo)	°C	690
Exhaust Temperature (After Turbo)	°C	570
Max. Exhaust Back Pressure	KPa	2
Exhaust Gas Flow	m ³ /min	416.25
Turbo Bellows Diameter	mm	DN250
Exhaust Flange Diameter	mm	DN250
Electrical System		
Charging Alternator Voltage	V	28
Charging Alternator Capacity	A	55
Starting Voltage	V	24
Starting Motor Capacity	kW	13
Minimum Battery Capacity	Ah	4*200
Engine Dimension		
Length	mm	3096
Width	mm	1459

Height	mm	1820
Engine Dry Weight w/o Cooling System	kg	5100

- 1: All engine parameters are in accordance with ISO3046, ISO8528.
- 2: All engine parameters are based on 25°C / 100kPa environment condition.
- 3: No power decrease with below 40°C environment temperature and 1500 meter altitude.
- 4: More than 40°C and 1500m above sea level , decrease 2% per 10°C , and 4% per 300m.
- 5: At calorific value 42700 kJ/kg + 5%, density 0,835 kg/dm³ , temperature 280 K.
- 6: Above data is only the testing data in our laboratory, it can't used to be the data on all contract.

Picture of Googol QTA3240-G6 Diesel Engine.

